

# MEGA Compressors

Quality Compressed Air Products

2 year warranty



## Industrial Series



TE-5060V



TK-5080V



TK-7580V

- Quiet operation
- Heavy duty two stage high efficient air compressors
- Durable cast iron pumps for performance and durability
- Splash type lubrication
- All cast iron pumps have steel valves for longer life
- Flywheels designed for excellent pump cooling
- All units are factory tested prior to shipment
- For commercial, automotive and industrial applications



TK-100120



TK-150120



TK-11030G

## Specifications

MODEL	HP	ACTUAL FAD-CFM		MAX. PSI	VOLTAGE/ PHASE	TANK SIZE	# OF CYLINDERS	PUMP RPM	NOISE LEVEL DBA	WEIGHT LBS.	REMARKS
		100 PSI	150PSI								
TE-5060V	5	15.7	15.4	175	230V/1PH	60	3	1300	80	400	VERTICAL
TK-5080V	5	19.4	19	175	SPECIFY	80	3	960	79	600	VERTICAL
TK-5080	5	19.4	19	175	SPECIFY	80	3	960	79	600	HORIZONTAL
TK-7580V	7.5	26.1	25.5	175	SPECIFY	80	2	995	78	650	VERTICAL
TK-7580	7.5	26.1	25.5	175	SPECIFY	80	2	995	78	650	HORIZONTAL
TK-100120	10	36.1	35.3	175	SPECIFY	120	3	843	80	950	HORIZONTAL
TK-150120	15	52.3	51.5	175	SPECIFY	120	3	668	80	1100	HORIZONTAL
TK-200120	20	69.8	68.8	175	SPECIFY	120	3	890	82	1160	HORIZONTAL
TK-250240	25	87.7	86.1	175	SPECIFY	240	4	542	78	1500	HORIZONTAL
TK-300240	30	100.8	99	175	SPECIFY	240	4	650	80	1500	HORIZONTAL
TK-11030G	11	19.4	19	175	11 HP GAS	30	3	960	90 RUN/82 IDLE	450	ELECTRIC START

Factory mounted options available upon request. Specialty units available upon request.

# MEGA Compressors

Quality Compressed Air Products

2 year warranty



## Contractor Series



DP-2004V



DP-2022H

- Direct Drive Units have splash lubricated pump with cast iron sleeve for longer life
- Belt Drive Units have durable cast iron pumps
- Splash type lubrication
- All cast iron pumps have steel valves for longer life
- Flywheels designed for excellent pump cooling
- Manual reset for overload protection
- Dual control-start/stop with pressure switch or constant speed operation for electric belt drive unit
- All gas units equipped with Honda Gas Engines
- Idle-down throttle control for gas belt drive unit
- All units are factory tested prior to shipment
- For farms and professional contractors



PUK-2008MDC



PUK-5508G



PUK-9008G



TUE-8008GE

## Specifications

MODEL	HP	ACTUAL FAD-CFM		MAX. PSI	VOLTAGE/ PHASE	TANK SIZE	NOISE LEVEL DBA	WEIGHT LBS.	REMARKS
		40 PSI	90 PSI						
DP-2004V	2	6.0	4.6	125	115V/1PH	3.2	83	55	PAN-CAKE
DP-2022H	2	6.0	4.6	125	115V/1PH	4	83	65	TWIN-STACK
PUK-2008MDC	2	9.5	8.0	125	115V/1PH	8	70	200	TWIN-TANK
PUK-5508G	5.5	12.5	10.5	125	5.5 HP GAS	8	90 RUN/82 IDLE	190	TWIN-TANK
PUK-5520G	5.5	12.5	10.5	125	5.5 HP GAS	20	90 RUN/82 IDLE	190	20 GAL. PORTABLE
PUK-9008G	9	20.6	17.6	125	9 HP GAS	8	90 RUN/82 IDLE	250	TWIN-TANK
TUE-8008GE	8	15.6	12.5	175	8 HP GAS	8	90 RUN/82 IDLE	250	ELECTRIC START